

## Model PI-700

Universal VOC Gas Sensor



Scrolling Full Message/Text Display



Photo Ionization Detector (PID)  
(shown as PN 967-PB4520-010 in SS junction box)



## Description

Model PI-700 is a non-intrusive “Smart” sensor that use photo-ionization detector technology to monitor VOC gases over ranges from 0-10 ppm to 0-1,000 ppm. In the PI-700 sensor design, Detcon has successfully converted the sensitive laboratory style PID technology into a rugged, environmentally insensitive, and long-life industrial gas sensor. The plug-in, field replaceable detector features over-sized gold-plated connections that help prevent corrosion. The PI-700’s rugged framework includes an electro-polished 316 stainless steel housing with fully encapsulated electronics and dual layer surge protection. This innovative design virtually eliminates sensor failure due to water ingress, corrosion, vibration, and transient spikes. A primary feature of the Model PI-700 is embedded intuitive software that simplifies operator interface by guiding the user through routine calibration, configuration, and fault diagnostic functions using a built-in alpha/numeric display. The Model PI-700 is equipped with standard analog 4-20mA, and Modbus™ RS-485 outputs. Among its unique features is a wireless option that can be used with Detcon’s SmartWireless® product line. Additional integration options include a Remote Alarm Module (RAM) and HART. Detcon’s PID sensors have a long shelf life and are supported by an industry leading warranty.

## Applications

- Pharmaceutical industry
- Power plants
- Chemical industry
- Air quality
- Refineries and petrochemical plants
- Solvent recovery systems
- Waste water treatment plants
- Marine and off-shore oil wells
- Pulp and paper industry
- Painting and coating operations

## Features

### Failsafe User-Friendly Interface

- LED Display (With Antiglare Cover)
- Full Text Display Method
- Non-intrusive Interface
- Auto Zero/Auto Span
- Pre-emptive Fault Diagnostics

### Environmentally Bulletproof

- Electropolished 316SS Construction
- 100% Epoxy Encapsulated Circuitry
- Bulletproof I/O Protection
- Water-Proof, Corrosion-Proof, Vibration-Proof

### Modular and Serviceable

- Modular Design
- Plug and Play Components
- Quick Thread Release (For Sensor Replacement)
- Integral Calibration Port



# Model PI-700

## Universal VOC Gas Sensor

### System Specifications

#### Sensor Type

Continuous diffusion/adsorption  
Photo Ionization Detector (PID)  
Plug-in replaceable intelligent type (with replacement lamp)

#### Sensor Life

2 years typical

#### Measurement Range

Gas Dependent, ranges as low as 0-10 ppm  
or as high as 0-1,000ppm (consult Detcon)

#### Accuracy/Repeatability

±10% of reading or ±2% of range (greater of)

#### Response Time

T50 <30 seconds; T90 <60 seconds

#### Outputs

Linear 4-20 mA DC  
RS-485 MODBUS-RTU

#### Electrical Classification

Explosion proof  
CSA and US (NRTL)  
Class I, Division 1, Groups A, B, C, D T4 (Tamb = -20°C to +55°C)  
Class I, Zone 1, Group IIC, T4  
ATEX and IECEx  
II 2G Ex db ia IIC T4 Gb (Tamb = -20°C to +55°C)

#### Ingress Protection

NEMA 4X, IP66

#### Safety Approvals

cCSAus  
ATEX  
CE Marking

#### Warranty

PLUG-IN DETECTOR - 1 YEAR  
TRANSMITTER - 2 YEARS

### Environmental Specifications

#### Operating Temperature Range

-4°F to +122°F; -20°C to +55°C

#### Storage Temperature Range

-4°F to +122°F; -20°C to +55°C

#### Operating Humidity Range

0-100% RH non-condensing

Specifications subject to change without notice

### Order Guide

Specify junction box options (below)

PN 967-PB5520-010	PI-700-VOC Sensor Assembly (no junction box)
PN 967-PB1520-010	PI-700-VOC Sensor Assembly with Aluminum Junction Box
PN 967-PB4520-010	PI-700-VOC Sensor Assembly with 316 SS Junction Box
PN 967-PM5520-01K	PI-701-VOC Sensor Assembly (no junction box)
PN 967-PM1520-01K	PI-701-VOC Sensor Assembly with Aluminum Junction Box
PN 967-PM4520-01K	PI-701-VOC Sensor Assembly with 316 SS Junction Box
PN 967-PB5520-0X5	PI-700-VOC Special Low Range Sensor Assembly with 316 SS Junction Box

### Mechanical Specifications

#### Dimensions

7"H x 2.2" Dia.; 178mmH x 65mm Dia. (sensor assembly only)  
11"H x 6.1"W x 3.75"D; 280mmH x 155mmW x 96mmD (with junction box)  
Mounting holes (J-box) 5.5"; 140mm center to center

#### Weight

2 lbs; 0.907kg (sensor only)  
6 lbs; 2.72kg (w/aluminum j-box)  
9 lbs; 4.08kg (w/stainless steel j-box)

### Electrical Specifications

#### Power Input

11-30 VDC

#### Power Consumption

Maximum = 65mA (1.6 watts)

#### Inrush Current

1.67A @ 24V

#### RFI/EMI Protection

Complies with EN50270

#### Analog Output

Linear 4-20mA DC (1,000 ohms max loop load @ 24VDC)  
0mA All Fault Diagnostics  
2mA In-Calibration  
4-20mA 0-100% full-scale  
22mA Over-range condition

#### Serial RS-485 Output

RS-485 Modbus™ RTU

#### Baud Rate

9600 BPS (9600,N,8,1 Half Duplex)

#### Status Indicators

4-digit LED display with gas concentration  
Full-script menu prompts for AutoSpan,  
Set-up Options, and Fault Reporting

#### Faults Monitored

Loop, Input Voltage,  
Zero, Missing Sensor,  
Processor, Memory, Calibration

#### Cable Requirements

Power/Analog  
3-wire shielded cable  
Maximum distance is 13,300 feet with 14 AWG  
Serial Output  
2-wire twisted-pair shielded cable specifically for use with RS-485 installations  
Maximum distance is 4,000 feet to last sensor

#### I/O Protection

Over-voltage, Miswiring, EMI/RFI Immunity

### Integration Options

Remote Alarm Module (Remote Operation and 2 Alarm Relays plus Fault)  
Hart Integration Module (Hart Communication Protocol version 7.0, HART Registered)

Teledyne Detcon quality assurance programmes demand the continuous assessment and improvement of all Teledyne Detcon products. Information in this leaflet could thus change without notification and does not constitute a product specification. Please contact us or our representative if you require more details.



**AMERICAS**  
14880 Skinner Rd  
Cypress, TX 77429  
USA  
Tel.: +1 713-559-9200

**EMEA**  
ZI Est, Rue Orfila,  
CS 20417  
62027 ARRAS CEDEX, France  
Tel.: +33-3-21-60-80-80

**ASIA PACIFIC**  
Room 04, 9th Floor, 275 Ruijing  
Road,  
Xuhui District, Shanghai, China  
TGFD\_APAC@teledyne.com