



Model CX-IR

Infrared LEL Gas Detectors



Description

Detcon Model CX-IR gas detection sensors are easily and economically deployable in both permanent and temporary installations. These low power sensor assemblies utilize infrared technology for combustible hydrocarbons. Model CX-IR sensors are equipped with standard analog 4-20mA, and Modbus™ RTU RS-485 outputs and can be used with Detcon's SmartWireless® Site Sentinel CX/CXT Controllers as well as other Detcon control systems. Relay and battery options available.

Model DM-IR Series sensors feature non-intrusive operator interface and comprehensive fault diagnostics. The sensor is packaged in an electro-polished 316 stainless steel housing fitted with a 3/4 inch NPT thread. The plug-in, field replaceable sensor cell features large surface area gold-plated pins that reduce the effects of corrosion in harsh industrial environments. Signal conditioning electronics are completely encapsulated in the sensor housing adding a high level of durability. This innovative design virtually eliminates sensor failure due to water ingress, corrosion, vibration, and transient spikes. The packaging is XP-intrinsically safe. A primary feature of the Model CX-IR is embedded intuitive software that simplifies operator interface by guiding the user through routine calibration, configuration, and fault diagnostic functions using a built-in alpha/numeric display.

Each sensor is shipped with a splash guard with integral calibration port. Detcon's IR combustible hydrocarbon sensors have a long shelf life and are supported by an industry-leading warranty.

Features

- Low Power Infrared Gas Detection Sensors
- Built-in Display
- Class I, Div. 1, Groups C, & D
- Non-intrusive Magnetic Interface
- Built-in Diagnostics
- Fully Encapsulated Electronics
- Electropolished 316SS Construction
- Quick Thread Release (for sensor replacement)
- Relays optional
- Battery power options

Applications

- Oil and Gas Drilling Rigs
- Work-over and pulling units
- Oil and Gas Production
- Turn-a-rounds in Refining and Petrochemical Plants
- One year run time on a single battery charge



Model CX-IR

Infrared LEL Gas Detectors

System Specifications

Sensor Type

Continuous diffusion/adsorption
Non-dispersive Infrared Optical (NDIR) - Combustible Gas
Sub-miniature plug-in field replaceable

Sensor Life

5 years typical

Measurement Range

0-100% LEL (lower explosive limit)

Accuracy/Repeatability

±3% 0-50% LEL; ±5% 51-100% LEL

Response Time

T50 < 10 seconds, T90 < 30 seconds

Outputs

Linear 4-20 mA DC
RS-485 Modbus™
3 Relays - alarm 1, 2, fault, contacts 5 amp (optional)

Electrical Classification

Explosion proof
Class I, Division 1, Groups C, D (Tamb = -40°C to +60°C)
Class I, Zone 1, Group IIB
Ex db ib IIB T4 Gb (Tamb = -40°C to +60°C)

Safety Approvals

cCSAus Performance to ISA 12.13.01-2000 and CSA 22.2 #152
ATEX
CE Marking
IECEX

Warranty

Plug-in detector - 2 years
Transmitter - 2 Years

Environmental Specifications

Operating Temperature Range

-40°F to +140°F; -40°C to +60°C

Storage Temperature Range

-40°F to +140°F; -40°C to +40°C

Operating Humidity Range

0-100% RH non-condensing

Mechanical Specifications

Dimensions

With Stainless Steel Mini J-Box
10"H x 3.62"W x 4.3"D; 254mmH x 92mmW x 109mmD
10"H x 5.5"W x 4.3"D; 254mmH x 140mmW x 109mmD (with XP
Power Switch)
12.2"H; 310mmH (with splashguard)

Weight

5.2 lbs/2.36 kg

Electrical Options

Power Input

9-30 VDC
Internal "D" Size Disposable Battery Pack (optional)
Lithium Ion Rechargeable Battery Pack (optional for CSA units only)

Power Consumption

100mW (Typical); 660mW (Max)

RFI/EMI Protection

Complies with EN50270

Analog Output

Linear 4-20mA DC (750 ohms max loop load @ 24VDC)
0mA All Fault Diagnostics
4-20mA 0-100% full-scale
22mA Over-range condition

Serial RS-485 Output

RS-485 Modbus™ RTU

Baud Rate

9600 BPS (9600,N,8,1 Half Duplex)

Status Indicators

4-digit LED display with gas concentration & fault

Faults Monitored

Missing Sensor, Zero,
Calibration

Cable Requirements

Power/Analog
3-wire shielded cable
Maximum distance is 13,300 feet with 14 AWG
Serial Output (optional)
2-wire twisted-pair shielded cable specifically for use with
RS-485 installations
Maximum distance is 4,000 feet to last sensor

I/O Protection

Over-voltage, Miswiring, EMI/RFI Immunity

Accessory Options

Tripod for Mounting (specify pole mount and/or leg mount
brackets)
Mini Tripod for Mounting (specify pole mount and/or leg mount brackets)

Specifications subject to change without notice

Order Guide

Part Number

96C-IR0402-100

Description

Model CX-IR, 0-100 % LEL Combustible in Stainless Steel Mini Junction Box

Teledyne Gas & Flame Detection quality assurance programmes demand the continuous assessment and improvement of all our products. Information in this leaflet could thus change without notification and does not constitute a product specification. For more information, please contact us or your company representative



AMERICAS
4055 Technology Forest Blvd.
The Woodlands,
TX 77381, USA
Tel.: +1-713-559-9200
Fax: +1-713-893-6729

EMEA
ZI Est, Rue Orfila,
CS 20417
62027 ARRAS CEDEX, France
Tel.: +33-3-21-60-80-80
Fax: +33-3-21-60-80-00

ASIA PACIFIC
290 Guiqiao Road
Pudong, Shanghai 201206
People's Republic of China
Tel.: +86-21-3127-6373
Fax: +86-21-3127-6365